### sensonic

## LD230 Custormer Display

### Clear, Easy-to read

Vacuum Fluorescent Display

stand-alone model with 2 poles

\*\*\* UFD DISPLAY \*\*\* \*\*HAVE A NICE DAY AN



stand-alone model with stretching pole







attached to base without poles

- supports 11 command model included EPSON andlogic control command.
- power supply from 5V to 12V to prevent any mindless use of improper power input.
- 20-columnx2 line dot matrix in a wide viewing angle.
- Easy connectivity to a wide range of POS products.
- OPOS/JPOS driver is standard.




round base and pole adapter are for optional




# LD230 custormer display

#### **Specifications**

general	display method	vacuum fluorescent display ( blue-green)
	number of characters	40 (20 columns x 2 lines)
	brightness	500-1000 cd/m2
	character font	5 x 7 dot matrix, cursor
	character type	95 alphanumeric, 32 international characters
	character size	5.5(H)x9.2(W)mm
	dot size (XxY)	0.86 x 1.2mm
	download characterts	9 characters
	panel dimension	220(W)x50(D)x87(H)mm
	pole dimension	per support: 130(L)x34.5(dia)mm
	base dimension	217(W)x106(D)x33(H)mm
	viewing angle	max 90°
	horizontal rotation	max 355°
	weight	approx 980 grams
commands mode		UITIMATE, LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
language support		US English, Int'l English, Bosnia, Croatian, Czech, Danish, Dutch, Estonian, Faroese, Finnish, Flemish, French, Fr Canadian, German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak, Spanish, Swedish.
interface		RS-232 (serial)/USB
connection	baud rate	direct connection 9600 or 19,200 bps
reliability	MTBF	30,000 hours
power	consumption	5~12VDC





119.9

35

